



GKOWM01 15W

Product Overview

High performing GKOWM01 Wall Mounts feature a compact and sleek design that is perfect for providing security lighting in entryways, perimeters, and other outdoor areas. DLC Qualified with a superb efficacy of up to 121 lm/W, they are the perfect one-to-one replacement for incandescent fixtures. They are also UL Wet Location Listed, making them ideal for outdoor applications.



Key Features

CONSTRUCTION:

- Rugged die-cast aluminum housing.
- Housing has direct contact with the driver to help maintain low temperature and long lifespan.
- Housing is completely sealed against moisture and environmental contaminants.

FINISH:

- The exterior is protected by a rust-resistant powder coat finish that provides superior resistance to weathering and corrosion.

OPTICS:

- Light engines are available in standard 4000K and 5000K configurations.
- Light output of up to 1,820 Lumens, replaces a 100W incandescent.
- Impact and UV-resistant polycarbonate lens is precisely designed to give a specific light distribution, maximizing efficiency and application spacing.

ELECTRICAL:

- Universal 120-277V input voltage.
- THD: $\leq 20\%$, Power Factor: $\geq 90\%$.

CONTROLS:

- Button photocell for further energy savings included by default - PO 120-277V.

INSTALLATION:

- Wall mount or junction box mount options are available.
- Easy installation with integrated level bubble.

LIFESPAN:

- Estimated 50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

LISTINGS:

- DesignLights Consortium® (DLC) qualified.
- UL listed for wet locations.
- Rated for ambient operating temperature -40°F to 122°F (-40°C to 50°C).



Performance Data

Lumen Output

System Watts	Lens	4000K(70CRI)		5000K(70CRI)	
		Lumens	Efficacy	Lumens	Efficacy
15W	Clear	1700lm	113lm/W	1750lm	117lm/W
15W	Frosted	1800lm	120lm/W	1820lm	121lm/W

Dimensions & Weight

GKOWM01: 15W



Weight:
15W: 1.87lb

Ordering Information

Wall Mount Series GKOWM01					Example: GKOWM15W27V50KDPOF		
Fixture Type	Wattage	Voltage	CCT	Finish	Photocell	Lens	
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
GKOWM	15W	27V 120-277V	40K 4000K 50K 5000K	D Dark Bronze B Black W White	PO 120-277V Photocell Blank Without Photocell	F Frosted Lens Blank Clear Lens	

Note: Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification.