



## Product Overview

The new series GKOBLO1 bollard light provides illumination for outdoor applications requiring a light source with a low mounting height, such as building entryways, pathways, and pedestrian plazas. This stylish pathway light provides consistent 360 degree illumination while generating no uplight. A CCT tunable option is available for additional control over light output.

## Key Features

### CONSTRUCTION:

- Rugged die-cast aluminum housing in a stylish round design.
- Housing is completely sealed against moisture and environmental contaminants.

### FINISH:

- The exterior is protected by a rust-resistant polyester powder coat finish that provides superior resistance to weathering and corrosion.

### OPTICS:

- Fixed CCT: Light engines are available in standard 4000K and 5000K configurations.
- Tunable CCT: Light engines are available in standard 3000K, 4000K and 5000K configurations.
- Available in 3,100 Lumens, replacing a 100W metal halide.
- Complete 360 degree illumination with no uplight for superior lighting control.

### ELECTRICAL:

- Standard 120-277V input voltage.
- 1-10V dimming driver(s) as default.
- THD: ≤20%, Power Factor: ≥90%.

### CONTROLS:

- Optional emergency battery backup provides up to 90 minutes of operation during outages.
- Available with optional CCT adjustment controls.

### INSTALLATION:

- Robust anchor bolt ground installation system for straightforward pre-buried ground installation.
- An optional decorative base enhances the look of the fixture (by special order).

### WARRANTY:

- 5 Year Limited Warranty.

### LISTINGS:

- DesignLights Consortium® (DLC) qualified.
- Rated for ambient operating temperature -40°F to 113°F (-40°C to 45°C).



# Performance Data


## Lumen Output

System Watts	Voltage	Type	3000K (70CRI)		4000K (70CRI)		5000K (70CRI)	
			Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
26W	120-277V	Fixed CCT	---	---	3000lm	115 lm/W	3100lm	119 lm/W
26W	120-277V	Tunable CCT	2800lm	110 lm/W	3000lm	115 lm/W	3100lm	119 lm/W

## Electrical Data

Number of Drivers	Driver Current (mA)	Nominal Power (W)	Input Voltage (V)	Current (Amps)
1	670	26	120	0.22
		26	208	0.13
		26	240	0.11
		26	277	0.09

## Dimensions



## Ordering Information

Bollard Light Series GKOBLO1					Example: GKOBLO126W27V50KD		
Fixture Type	Wattage	Voltage	CCT	Finish	Battery Backup (Optional)	Internal Code	
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
GKOBLO1	26w	27V 120-277V	40K 4000K 50K 5000K DDK CCT Tunable	D Dark Bronze B Black W White SG Silver Grey	B With Emergency Battery Blank Without Emergency Battery	Blank Alphanumeric	