



2X2 :
25W / 30W / 40W




1X4 :
25W / 30W / 40W



2X4 :
30W / 40W / 50W

Product Overview

The DLC Premium Power & CCT Tunable panels allow the lighting professional to adjust the power and CCT during installation, while the DLC Listed Emergency panels include a battery backup in case of a power outage.



Key Features

CONSTRUCTION:

- Durable aluminum frame and cold rolled steel backplate in a slim and modern design.

FINISH:

- The exterior is protected by a white rust-resistant powder coat finish that provides superior resistance to weathering and corrosion.

OPTICS:

- Standard 110° beam angle.
- Light engines are available in standard 3500K, 4000K, and 5000K configurations.
- A range of lumen options available from 3,125 to 5,971 Lumens.
- PS diffuser ensures comfortable light distribution, with no glare or yellowing.

ELECTRICAL:

- Standard 120-277V input voltage.
- Standard 1KV surge protection.
- 0-10V dimming driver(s) as default.
- Flicker-free driver with 3% stroboscopic index prevents flicker during the lighting and dimming process.
- Power & CCT Tunable Panel THD: <10%, Power Factor: >90%.
- Emergency Panel THD: <20%, Power Factor: >90%.

CONTROLS:

- Power & CCT Tunable Panel: Power and CCT may be adjusted during installation using a switch on the fixture housing.
- Emergency Panel: Includes an emergency battery backup that provides up to 90 minutes of operation during outages.
- Bluetooth networked controls that are DLC NLC qualified, utilizing a Bluetooth SIG mesh network operated with IOS and web, optional for all models.

INSTALLATION:

- Suitable for recessed installation.
- 4 pre-installed protective brackets help prevent damage during earthquakes.

WARRANTY:

- 5 Year Limited Warranty.

LISTINGS:

- DesignLights Consortium® (DLC) Premium and Standard qualified.
- UL listed for damp locations.
- Power & CCT Tunable Panel is rated for ambient operating temperature -13°F to 104°F (-25°C to 40°C).
- Emergency Panel is rated for ambient operating temperature 32°F to 104°F (0°C to 40°C).


Performance Data

Lumen Output

System Watts	Type	Size	3500K(80CRI)		4000K(80CRI)		5000K(80CRI)	
			Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
25W	Tunable	2x2	3125lm	126lm/W	3125lm	126lm/W	3125lm	126lm/W
30W	Tunable	2x2	3750lm	126lm/W	3750lm	126lm/W	3750lm	126lm/W
40W	Tunable	2x2	5169lm	126lm/W	5169lm	126lm/W	5169lm	126lm/W
25W	Tunable	1x4	3125lm	130lm/W	3125lm	130lm/W	3125lm	130lm/W
30W	Tunable	1x4	3750lm	130lm/W	3750lm	130lm/W	3750lm	130lm/W
40W	Tunable	1x4	5172lm	130lm/W	5172lm	130lm/W	5172lm	130lm/W
30W	Tunable	2x4	3750lm	124lm/W	3750lm	124lm/W	3750lm	124lm/W
40W	Tunable	2x4	5000lm	124lm/W	5000lm	124lm/W	5000lm	124lm/W
50W	Tunable	2x4	5835lm	124lm/W	5835lm	124lm/W	5835lm	124lm/W
40W	Emergency	2x2	4407lm	114lm/W	4469lm	111lm/W	4591lm	114lm/W
50W	Emergency	2x4	5853lm	113lm/W	5893lm	114lm/W	5971lm	116lm/W


Dimensions & Weight

2x2 Tunable / 2x2 Emergency




Weight
Tunable: 4.41lb.
Emergency: 5.51lb.

2x4 Tunable / 2x4 Emergency



Weight
Tunable: 9.04lb.
Emergency: 10.8 lb.

1x4 Tunable



Weight
Tunable: 5.07lb.

Ordering Information

LED Panel Series GKOPL										Example: GKOPL24B27V30WPCPB					
Fixture Type	Size		Backlit	Voltage		Wattage		CCT		Emergency Battery		DLC		Driver Type	
<input type="text"/>	<input type="text"/>		<input type="text"/>	<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>	
GKOPL	22	2x2	B Backlit	27V	120-277V	25W	PC Tunable		Blank	Without Battery	P Premium	B	Type B		
	14	1x4				30W									
	24	2x4				40W									
	22	2x2				30W									
	24	2x4				40W	35K 3500K		EM	With Battery	S Standard				
						50W	40K 4000K								
							50K 5000K								

Note: Emergency LED Panels are only stocked in a 4000K configuration. Other CCTs are available by special order only.



100 E. Crossroads Pkwy. Ste. C
 Bolingbrook, IL 60440
 Phone: 630-793-9449
 Web: www.gkoled.com