

## **DUSK TO DAWN**

## **SERIES GKODDG5**



### **Product Overview**

High performing GKODDG5 Dusk To Dawn lights are ideal for providing commercial and residential properties with general perimeter and security lighting. With durable die-cast aluminum housing and advanced LED technology, they are the perfect replacement for a traditional metal halide dusk to dawn. An optional mounting arm is available for increased reach.









### **Key Features**

#### CONSTRUCTION:

- Rugged die-cast aluminum housing.
- Housing is completely sealed against moisture and environmental contaminants.

#### FINISH

The exterior is protected by a rust-resistant polyester powder coat finish that provides superior resistance to weathering and corrosion.

#### OPTICS

- Light engines are available in standard 4000K and 5000K configurations.
- A range of lumen options available from 6,200 to 12,400 Lumens, replaces up to 250W metal halide.

#### ELECTRICAL:

- Standard 120-277V input voltage.
- 1-10V dimming driver(s) as default.
- THD:  $\leq$ 20%, Power Factor:  $\geq$ 90%.

#### CONTROLS

■ Twist-lock photocell included by default - P0 120-277V.

#### INSTALLATION:

- Pole mount or wall mount options are available.
- Optional mounting arm is available for increased reach.

#### WARRANTY:

■ 5 Year Limited Warranty.

#### LISTINGS:

- DesignLights Consortium® (DLC) Premium qualified.
- UL listed for wet locations.
- Rated for ambient operating temperature -40°F to 104°F (-40°C to 40°C).



## **Perfomance Data**

### Lumen Output


System Watts	Voltage	4000K(70CRI)		5000K(70CRI)	
		Lumens	Efficacy	Lumens	Efficacy
45W	120-277V	6200lm	138lm/W	6200lm	138lm/W
65W	120-277V	8800lm	135lm/W	8800lm	135lm/W
90W	120-277V	12400lm	138lm/W	12400lm	138lm/W


### **Electrical Data**

Number of Drivers	Driver Current (mA)	Nominal Power (W)	Input Voltage (V)	Current (Amps)
1	1100	45	120	0.38
		45	208	0.22
		45	240	0.19
		45	277	0.16
1	1630	65	120	0.54
		65	208	0.31
		65	240	0.27
		65	277	0.23
1	2270	90	120	0.75
		90	208	0.43
		90	240	0.38
		90	277	0.32

## **Dimensions & Weight**

#### GKODDG5: 45W / 65W / 90W






Weight 45W: 4.54 lb. 65W: 4.80 lb. 95W: 5.03 lb.

Mounting Arm - Dark Bronze



Mounting Arm - Silver Gray






100 E. Crossroads Pkwy. Ste. C Bolingbrook, IL 60440 **Phone:** 630-793-9449 **Web:** www.gkoled.com

## **Photometric Distribution**

### General



# **Ordering Information**

Dusk To Dawn	Series GKODD(	Example:GKODDG545W27V50KSGP0				
Fixture Type	Wattage	Voltage	сст	Finish	Photocell	Internal Code
GKODDG5	45W 65W 90W	<b>27V</b> 120-277V	<b>40K</b> 4000K <b>50K</b> 5000K	SG Silver Gray D Dark Bronze B Black W White	PO With Photocell	Blank Alphanumeric

