



NON-CUTOFF WALL PACK

SERIES GKOWP08



30W / 40W / 65W / 90W / 100W / 125W

Product Overview

Series GKOWP08 Non-Cutoff Wall Packs efficiently deliver lumens while consuming less energy than traditional metal halide technologies. GKOWP08 features a traditional non-cutoff design that offers superb vertical illumination. An integrated bubble level and convenient hinged door enable easy installation. 65W and 100W are available as Power & CCT Selectable models.



Key Features

CONSTRUCTION:

- Rugged die-cast aluminum housing.
- Housing has direct contact with the driver to help maintain low temperature and long lifespan.
- Housing is completely sealed against moisture and environmental contaminants.

FINISH:

- The exterior is protected by a rust-resistant powder coat finish that provides superior resistance to weathering and corrosion.

OPTICS:

- Light engines are available in standard 4000K and 5000K configurations.
- A wide range of lumen options available from 3,500 to 15,400 Lumens, replaces up to 400W metal halide.
- Impact and UV-resistant polycarbonate lens is precisely designed to give a specific light distribution, maximizing efficiency and application spacing.

ELECTRICAL:

- Universal 120-277V input voltage.
- 1-10V dimming driver(s) as default.
- THD: ≤20%, Power Factor: ≥90%.

CONTROLS:

- 65W and 100W are available with Power & CCT adjustment controls.
- Optional button photocell for additional energy savings - PO 120-277V.
- Optional emergency battery backup provides up to 90 minutes of operation during outages (only available for 65W).

INSTALLATION:

- Wall mount or junction box mount options are available.
- Easy installation with integrated level bubble and hinged door.

WARRANTY:

- 5 Year Limited Warranty.

LISTINGS:

- DesignLights Consortium® (DLC) qualified.
- UL listed for wet locations.
- Rated for ambient operating temperature -40°F to 104°F (-40°C to 40°C).



100 E. Crossroads Pkwy. Ste. C
Bolingbrook, IL 60440
Phone: 630-793-9449
Web: www.gkoled.com

Performance Data

Fixed Power & CCT Model Lumen Output

System Watts	Voltage	4000K(70CRI)		5000K(70CRI)	
		Lumens	Efficacy	Lumens	Efficacy
30W	120-277V	3500lm	117lm/W	3500lm	117lm/W
40W	120-277V	4800lm	120lm/W	4850lm	121lm/W
65W	120-277V	7800lm	120lm/W	7900lm	122lm/W
90W	120-277V	10800lm	120lm/W	10800lm	120lm/W
125W	120-277V	15400lm	123lm/W	15400lm	123lm/W

Power & CCT Selectable Model Lumen Output

System Watts	Voltage	3000K(70CRI)		4000K(70CRI)		5000K(70CRI)	
		Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
65W	120-277V	7700lm	118lm/W	8300lm	128lm/W	7900lm	122lm/W
100W	120-277V	11500lm	115lm/W	12000lm	120lm/W	11600lm	116lm/W

Power & CCT Selectable Model Wattage Output


LV1	LV2	LV3	LV4
100%	80%	60%	40%

Electrical Data

Number of Drivers	Driver Current (mA)	Nominal Power (W)	Input Voltage (V)	Current (Amps)
1	430	30	120	0.25
		30	208	0.14
		30	240	0.13
		30	277	0.11
1	640	40	120	0.33
		40	208	0.19
		40	240	0.17
		40	277	0.14
1	1100	65	120	0.54
		65	208	0.31
		65	240	0.27
		65	277	0.23
1	2270	90	120	0.75
		90	208	0.43
		90	240	0.38
		90	277	0.32
1	2500	100	120	0.83
		100	208	0.48
		100	240	0.42
		100	277	0.36
2	3260	125	120	1.04
		125	208	0.60
		125	240	0.52
		125	277	0.45

Dimensions & Weight

GKOWP08



Weight
30W: 6.327lb.
40W: 6.525lb.
65W: 6.724lb.
90W / 100W: 7.319lb.
125W: 8.157lb.

Ordering Information

Non-Cutoff Wall Pack Series GKOWP08										Example: GKOWP0830W27V50KD	
Fixture Type <div></div>	Wattage <div></div>	Voltage <div></div>	CCT <div></div>		Finish <div></div>	Photocell (Optional) <div></div>		Battery Backup (Optional) <div></div>		Power & CCT Selectable <div></div>	Internal Code <div></div>
GKOWP08	30W	27V 120-277V	40K 4000K 50K 5000K	D Dark Bronze² B Black W White	P0 120-277V Photocell	Blank Without Photocell	B Emergency³ Battery Backup Blank Without Emergency Battery Backup	AD With Adjustment Controls Blank Without Adjustment Controls	Blank Alphanumeric		
	40W										
	65W										
	90W										
	125W										
	65W 100W	27V 120-277V	DDK Power & CCT¹ Selectable								

Note: 1. Power & CCT Selectable option is only available for 65W and 100W models with Adjustable Power & CCT.
2. Default finish is dark bronze. All other finishes are special order only.
3. Emergency battery backup is only available for 65W.