



Product Overview

GKOALG5 Area Lights are the cost-effective area lighting solution for mounting heights ranging from 26' to 50', featuring a low-profile, compact housing in an attractive design. An optional twist-lock photocell or multi-level motion sensor is available for additional energy savings, and an optional backlight glare shield minimizes light spillover.



Key Features

CONSTRUCTION:

- Rugged single-piece, die-cast aluminum housing with integral heat sink fins.
- Housing has direct contact with the driver to help maintain low temperature and long lifespan.
- 3G vibration rated for areas with traffic, meeting ANSI standards C136.31.
- Housing is completely sealed against moisture and environmental contaminants.

OPTICS:

- Type III, IV, V light distribution available.
- Light engines are available in standard 4000K and 5000K configurations.
- A wide range of lumen options available from 13,900 to 42,000 Lumens, replaces up to 1,000W metal halide.
- Impact and UV-resistant polycarbonate lens is precisely designed to give a specific light distribution, maximizing efficiency and application spacing.
- Optional backlight glare shield is available for minimizing lighting spillover in order to comply with local ordinances.

ELECTRICAL:

- Universal 120-277V or 347-480V input voltage.
- Integrated 6KV surge protection with additional 10KV surge protection for 120-277V and 20KV surge protection for 347-480V.
- 0-10V dimming driver(s) as default.
- THD: ≤20%, Power Factor: ≥90%.

CONTROLS:

- Optional multi-level motion sensor - BRI823 or BRI619 (120-277V 100W only) (not compatible with twist-lock photocell).
- Optional twist-lock photocell - P0 120-277V or P4 480V (not compatible with multi-level motion sensor).
- Optional motion sensor remote control - while not mandatory for programming the motion sensor, you avoid having to remove the fixture driver cover for programming, can program multiple sensors with ease, and can program the sensor after the fixture is installed.

INSTALLATION:

- Suitable for mounting heights ranging from 26'-50' in area lighting applications.
- Fixed and adjustable round and square pole, slipfitter, wall, and yoke mount are available.
- Designed to be suitable for installation by only one person.

WARRANTY:

- 5 Year Limited Warranty.

LISTINGS:

- DesignLights Consortium® (DLC) Premium qualified.
- UL listed for wet locations.
- Rated for ambient operating temperature -40°F to 104°F (-40°C to 40°C).

Performance Data

Lumen Output

| Wattage | Voltage | Distribution Type | 4000K(70CRI) | | 5000K(70CRI) | |
|---------|---------------------|-------------------|--------------|----------|--------------|----------|
| | | | Lumens | Efficacy | Lumens | Efficacy |
| 100W | 120-277V / 347-480V | 3 | 14100lm | 141lm/W | 14100lm | 141lm/W |
| | | 4 | 14000lm | 140lm/W | 13900lm | 139lm/W |
| | | 5 | 14200lm | 142lm/W | 14200lm | 142lm/W |
| 150W | 120-277V / 347-480V | 3 | 21000lm | 140lm/W | 21000lm | 140lm/W |
| | | 4 | 20500lm | 137lm/W | 20500lm | 137lm/W |
| | | 5 | 21000lm | 140lm/W | 21000lm | 140lm/W |
| 180W | 120-277V / 347-480V | 3 | 25000lm | 139lm/W | 25000lm | 139lm/W |
| | | 4 | 25000lm | 139lm/W | 25000lm | 139lm/W |
| | | 5 | 26000lm | 144lm/W | 26000lm | 144lm/W |
| 250W | 120-277V / 347-480V | 3 | 35000lm | 140lm/W | 35000lm | 140lm/W |
| | | 4 | 35000lm | 140lm/W | 35000lm | 140lm/W |
| | | 5 | 36000lm | 144lm/W | 36000lm | 144lm/W |
| 300W | 120-277V / 347-480V | 3 | 42000lm | 140lm/W | 42000lm | 140lm/W |
| | | 4 | 41000lm | 137lm/W | 41000lm | 137lm/W |
| | | 5 | 42000lm | 140lm/W | 42000lm | 140lm/W |

BUG Rating

| Wattage | Voltage | Distribution Type | B | U | G |
|---------|---------------------|-------------------|---|---|---|
| 100W | 120-277V / 347-480V | 3 | 2 | 0 | 2 |
| | | 4 | 3 | 0 | 3 |
| | | 5 | 4 | 0 | 2 |
| 150W | 120-277V / 347-480V | 3 | 3 | 0 | 3 |
| | | 4 | 3 | 0 | 3 |
| | | 5 | 4 | 0 | 2 |
| 180W | 120-277V / 347-480V | 3 | 3 | 0 | 3 |
| | | 4 | 3 | 0 | 3 |
| | | 5 | 4 | 0 | 2 |
| 250W | 120-277V / 347-480V | 3 | 4 | 0 | 4 |
| | | 4 | 4 | 0 | 4 |
| | | 5 | 5 | 0 | 3 |
| 300W | 120-277V / 347-480V | 3 | 4 | 0 | 4 |
| | | 4 | 4 | 0 | 5 |
| | | 5 | 5 | 0 | 3 |

Electrical Data

| Number of Drivers | Driver Current (mA) | Nominal Power (W) | Input Voltage (V) | Current (Amps) |
|-------------------|---------------------|-------------------|-------------------|----------------|
| 1 | 850 | 100 | 120 | 0.83 |
| | | 100 | 208 | 0.48 |
| | | 100 | 240 | 0.42 |
| | | 100 | 277 | 0.36 |
| | | 100 | 347 | 0.29 |
| | | 100 | 480 | 0.21 |
| 1 | 1200 | 150 | 120 | 1.25 |
| | | 150 | 208 | 0.72 |
| | | 150 | 240 | 0.63 |
| | | 150 | 277 | 0.54 |
| | | 150 | 347 | 0.43 |
| | | 150 | 480 | 0.31 |
| 1 | 960 | 180 | 120 | 1.50 |
| | | 180 | 208 | 0.87 |
| | | 180 | 240 | 0.75 |
| | | 180 | 277 | 0.65 |
| | | 180 | 347 | 0.52 |
| | | 180 | 480 | 0.38 |

Electrical Data


| Number of Drivers | Driver Current (mA) | Nominal Power (W) | Input Voltage (V) | Current (Amps) |
|-------------------|---------------------|-------------------|-------------------|----------------|
| 1 | 1200 | 250 | 120 | 2.08 |
| | | 250 | 208 | 1.20 |
| | | 250 | 240 | 1.04 |
| | | 250 | 277 | 0.90 |
| | | 250 | 347 | 0.72 |
| | | 250 | 480 | 0.52 |
| 1 | 1500 | 300 | 120 | 2.50 |
| | | 300 | 208 | 1.44 |
| | | 300 | 240 | 1.25 |
| | | 300 | 277 | 1.08 |
| | | 300 | 347 | 0.86 |
| | | 300 | 480 | 0.63 |

EPA of Series GKOALG5 Area Light


| | 1 | 2 @ 90° | 2 @ 120° | 2 @ 180° | 3 @ 90° | 3 @ 120° | 4 @ 90° |
|-------------|--------|---------|----------|----------|---------|----------|---------|
| 100W | 0.2751 | 0.5267 | 0.7321 | 0.6164 | 0.9577 | 0.9837 | 0.9577 |
| 150W / 180W | 0.3111 | 0.6343 | 0.6464 | 0.6222 | 0.9335 | 0.9696 | 0.9335 |
| 250W / 300W | 0.4097 | 0.7227 | 0.9919 | 0.8856 | 1.1986 | 1.3049 | 1.1986 |

Dimensions & Weight


100W (Adjustable Pole Mount)




100W (Slipfitter Mount)




100W (Wall Mount)




100W (Pole Mount)




100W (Yoke Mount)




150W / 180W (Adjustable Pole Mount)




150W / 180W (Slipfitter Mount)




150W / 180W (Wall Mount)



150W / 180W (Pole Mount)




150W / 180W (Yoke Mount)




Dimensions & Weight

**250W / 300W
(Adjustable Pole Mount)**




Net Weight
250W: 12.88lb.
300W: 13.32lb.

**250W / 300W
(Slipfitter Mount)**




Net Weight
250W: 13.3lb.
300W: 13.74lb.

**250W / 300W
(Wall Mount)**




Net Weight
250W: 15.81lb.
300W: 16.26lb.

**250W / 300W
(Pole Mount)**



Net Weight
250W: 13.56lb.
300W: 14.01lb.

**250W / 300W
(Yoke Mount)**



Net Weight
250W: 12.06lb.
300W: 12.51lb.




Lighting Distribution

GKOLED offers a complete set of optical systems to meet every site lighting requirement. These systems provide remarkable flexibility in precisely matching light distribution patterns to specific site requirements.

Type 3 optics produce an asymmetrical pattern that directs the majority of the light forward and equally on both sides of the luminaire. In a back-to-back configuration, it creates a rectangular pattern which can extend pole spacings.

Type 4 is suitable for applications where light is primarily required forward with minimal backlight. Typical installations include perimeter poles.

Type 5 optics produce a symmetrical square distribution pattern that distributes light equally on all sides of the luminaire. Type 5 luminaires are universal for most area lighting applications.



Mounting Information

Mounting Options



Pole Mount (4" and 5" Square and Round Poles)

Standard versatile mounting arm is simple to install and can be used with existing poles for retrofit installations.



Slipfitter Mount

An optional cast aluminum mast arm adaptor secures fixture head to nominal 2" (2-3/8" O.D. pipe size) horizontal steel tenon arm.



Wall Mount

Wall Mount is easy to install for direct wall mounting with 1/2" conduit wiring or standard J-Box mounting.



Yoke Mount

Die-cast aluminum yoke is easily adapted to many surfaces and adjusted to a range of fixture aiming angles.



Adjustable Pole Mount

Adjustable mounting arm is simple to install and can be used with existing poles for retrofit installations.

Mounting Accessories

| ROUND POLE CONNECTING PLATE • For square mount to be fixed to a round pole | | |
|----------------------------------------------------------------------------|--|--|
| | | |


Additional Accessories

| POLE BRACKET • For mounting one fixture on an existing pole | | | |
|-------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <p>4" Square Pole Mount with 2-3/8" O.D. Tenon NO. 4SQ-SP-D FINISH: Dark Bronze USE: For use with square, non-tapered steel and aluminum poles. Furnished with four 5/16" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p> | | <p>4" Round Pole Mount with 2-3/8" O.D. Tenon NO. 4SQR-SP-D FINISH: Dark Bronze USE: For use with round, non-tapered steel and aluminum poles. Furnished with three 3/8" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p> |
| | <p>5" Square Pole Mount with 2-3/8" O.D. Tenon NO. 5SQ-SP-D FINISH: Dark Bronze USE: For use with square, non-tapered steel and aluminum poles. Furnished with four 5/16" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p> | | <p>5" Round Pole Mount with 2-3/8" O.D. Tenon NO. 5SQR-SP-D FINISH: Dark Bronze USE: For use with round, non-tapered steel and aluminum poles. Furnished with three 3/8" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p> |
| | <p>2-3/8" O.D. Tenon Mount Adaptor for Yoke Fixtures NO. SP-TR-D FINISH: Dark Bronze USE: The 2-3/8" O.D. Tenon Mount Adaptor for Yoke Fixtures is designed to mount GKOLED light fixtures that are equipped with a yoke mount onto a 2-3/8" O.D. tenon. It may be utilized with the GKOLED flood light series of light fixture.</p> | | <p>Angle Adjustment Adaptor NO. SQA-AL04DA FINISH: Dark Bronze USE: This durable bracket is engineered as a versatile mounting option. Made from die-cast aluminum, it allows for optimal positioning of the light fixture to maximize the light effectiveness both vertically and horizontally.</p> |
| | <p>Horizontal Wall or Square or Round Pole Mount with 2-3/8" O.D. Tenon Bracket NO. SQ/R-SP-D FINISH: Dark Bronze USE: This tenon bracket can be installed onto a wall, square pole, or round pole. Provides wiring access and a built-in 2-3/8" O.D. tenon to mount a fixture with our adjustable slipfitter. Suggested 3/8" diameter bolts for mounting.</p> | | |

| WALL BRACKET • Attaches to any flat surface • Provides wiring access | | MID-POLE TENON BRACKET | |
|----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <p>90° Wall Mount Bracket with 2-3/8" O.D. Tenon NO. WM-SP-D FINISH: Dark Bronze USE: The 90° Wall Mount Bracket with 2-3/8" Tenon attaches a GKOLED flood light to almost any surface, wall, roof, or wood pole. Provides wiring access and a built-in 2-3/8" O.D. tenon to mount a fixture with our adjustable slipfitter. Suggested 3/8" diameter bolts for mounting. Mounting holes are spaced 3-1/4" apart.</p> | | <p>2-3/8" O.D. Horizontal Tenon Mid-Pole Bracket NO. SQ-SP-D FINISH: Dark Bronze USE: The 2-3/8" O.D. Horizontal Tenon Mid-Pole Bracket is designed to mount a light fixture that is equipped with an adjustable slipfitter onto a 2-3/8" O.D. horizontal tenon.</p> |

| ROUND EXTERNAL MOUNT HORIZONTAL TENON • To mount 2, 3, or 4 fixtures on an existing pole | | | |
|------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <p>Double 90° Horizontal Tenon Adaptor NO. R60-SP2-90-D FINISH: Dark Bronze USE: The Bracket is designed to mount over a 2-3/8" (60mm) O.D. vertical tenon. Two fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally.</p> | | <p>Triple 120° Horizontal Tenon Adaptor NO. R60-SP3-120-D FINISH: Dark Bronze USE: The Bracket is designed to mount over a 2-3/8" (60mm) O.D. vertical tenon. Three fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally.</p> |

Additional Accessories

| ROUND EXTERNAL MOUNT HORIZONTAL TENON • To mount 2, 3, or 4 fixtures on an existing pole | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  <p>Double 180° Horizontal Tenon Adaptor NO. R60-SP2-180-D FINISH: Dark Bronze USE: The Bracket is designed to mount over a 2-3/8" (60mm) O.D. vertical tenon. Two fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally.</p> |  <p>Quad 90° Horizontal Tenon Adaptor NO. R60-SP4-90-D FINISH: Dark Bronze USE: The Bracket is designed to mount over a 2-3/8" (60mm) O.D. vertical tenon. Four fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally.</p> |
|  <p>Triple 90° Horizontal Tenon Adaptor NO. R60-SP3-90-D FINISH: Dark Bronze USE: The Bracket is designed to mount over a 2-3/8" (60mm) O.D. vertical tenon. Three fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally.</p> | |

Accessories



MULTI-LEVEL MOTION SENSOR
Optional multi-level motion sensor detects occupancy in an area for additional energy savings.




MOTION SENSOR REMOTE CONTROL
Optional remote control programs the motion sensor with advanced lighting control options.



TWIST-LOCK PHOTOCELL AND RECEPTACLE
Optional 3 prong twist-lock photocell adds dusk to dawn function for additional energy savings.

Glare Shields

An optional backlight control provides reduced light spillover and increased visual comfort without compromising performance.

| | | | |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |
| Backlight Glare Shield | Small Size | Medium Size | Large Size |

Ordering Information

| Area Light Series GKOALG5 | | | | | | | Example: GKOALG5100W27V50KDPOSQT3S | | | |
|---------------------------|---------|------------------------------|------------------------|--------------------------------------------------------|--------------------------------------------------------------------------------------------|---------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------|--------------------|--|
| Fixture Type | Wattage | Voltage | CCT | Finish | Photocell (Optional) | Sensor (Optional) | Mounting | Photometry | Surge Protection | |
| GKOALG5 | 100w | 27V 120-277V 48V 347-480V | 40K 4000K 50K 5000K | D Dark Bronze* B Black W White SG Silver Gray | P0 120-277V Photocell P3 347V Photocell P4 480V Photocell Blank Without Photocell | M With Sensor Blank Without Sensor | SQ Square Pole Mount SP Slipfitter Mount WM Wall Mount YK Yoke Mount | T3 Type III Photometry T4 Type IV Photometry T5 Type V Photometry | S Surge Protection | |

Ordering Information

Area Light Series GKOALG5

Example: GKOALG5150W27V50KDP0SPT3

| Fixture Type | Wattage | Voltage | CCT | Finish | Photocell (Optional) | Sensor (Optional) | Mounting | Photometry |
|----------------------|----------------------|----------------------|----------------------|-----------------------|--------------------------------|-----------------------------|-----------------------------|-------------------------------|
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| GKOALG5 | 150W | 27V 120-277V | 40K 4000K | D Dark Bronze* | P0 120-277V Photocell | M With Sensor | SQ Square Pole Mount | T3 Type III Photometry |
| | 180W | 48V 347-480V | 50K 5000K | B Black | P3 347V Photocell | Blank Without Sensor | SP Slipfitter Mount | T4 Type IV Photometry |
| | 250W | | | W White | P4 480V Photocell | | WM Wall Mount | T5 Type V Photometry |
| | 300W | | | SG Silver Gray | Blank Without Photocell | | YK Yoke Mount | |

NOTE: *Default finish is dark bronze. All other finishes are special order only.